BEGA 31 369

Wall luminaire » Kopenhagen «



Project · Reference number

Date

Product data sheet

Application

Wall luminaire for many lighting tasks on or in buildings.

Luminaire with hand-blown crystal glass for brilliant light.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel Luminaire top made of copper Crystal glass Mounting plate with 2 fixing holes ø 5.5 mm · 70 mm spacing 1 cable entry for mains supply cable up to \emptyset 10,5 mm max. $3 \times 1,5^{\circ}$ Connection terminal 2.5 Earth conductor connection Lampholder E 27 Safety class I Protection class IP 23 Protected against granular foreign bodies > 12 mm and showers up to 60° **₹10** ♠ – Safety mark $\mathbf{C}\mathbf{E}$ – Conformity mark Weight: 3.4 kg

Copper

The luminaire parts made of solid copper are delivered with the metal's natural surface colour. Time and weather factors create the natural patina characteristic for copper.

Lamps

Luminaire with lampholder E 27 Lamp output max. 100 W

For this luminaire we recommend the following BEGA LED lamps:

13509 LED 7 W · 805 lm · 2700 K 13547 LED 7 W · 805 lm · 2700 K dimmable 13511 LED 8 W · 1055 lm · 2700 K 13562 LED 12 W · 1520 lm · 2700 K dimmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.



