


Wall Spot

Cat. No. WS Cat. No. WS/R Cat. No. WSGU











The Wall Spot has been designed to be mounted on walls and provide directional light for pathways and structural elements of a building. This luminaire has a fully adjustable head allowing 360 degree rotation and 0-90 degree elevation.

This luminaire is machined from a choice of 10mm solid aluminium with a UV stable powder coated finish, solid copper and 316 stainless steel with a clear, tempered, flush fit glass lens and high temperature silicone gaskets.

The Retro is a 110/240-12 ac mains option suited to an installation where mounting a transformer is a problem, e.g. a brick wall where there is only the cable potruding out of the wall and it is not an option to recess the transformer, or when replacing an existing light fitting. The base increases in size to accomodate the encapsulated IP66 dimmable transformer.

A GU10 version of this luminaire is also available for line voltage lamps. However, a longer body is needed to accommodate the longer lamp.

Ordering Information

Luminaire Type Material/Finish Accessories WS - Wall Spot BK - Black CJK150 - Cable Joint Kit WS/R - Wall Spot Retro GG - Glare Guard BZ - Bronze WSGU - Wall Spot GU10 CT - Corten HCL - Hex Cell Louvre DG - Dark Grev LENSSTEPF - Frosted Lens OG - Olive Green WBAP - Wall Box STAR - Silver Star Adaptor Plate WB - White Birch WH - White COP - Copper SS - Stainless Steel Ordering example: WS BK - Wall Spot in Black WS/R COP - Wall Spot Retro in Copper WSGU SS - Wall Spot GU10 in Stainless Steel



LENSSTEPF - Frosted Lens

(accessories ordered separately)

Luminaire Construction

CNC machined from one of the following metals:

Aluminium

High corrosion resistant aluminium with chromate substrate and high UV resistant polyester powder coat.

Body: 63.5mm (2½") x 10mm (3/8") aluminium tube.

End cap: solid aluminium 63.5mm (2½")

Base: 2mm (1/16") hand spun aluminium. Back plate: cast from virgin high corrosion resistant CC401 low copper aluminium alloy.

Colours:

Black, Bronze, Corten, Dark Grey, Olive Green, Silver Star, White Birch, White.

Body: 63.5mm (2½") x 10mm (3/8") copper tube.

End cap: solid copper 63.5mm (21/2") rod. Base: 2mm (1/16") hand spun copper.

Back plate: forged brass.

316 Stainless Steel

Body: 63.5mm (2½") x 10mm (3/8") stainless steel tube.

End cap: solid stainless steel 63.5mm $(2\frac{1}{2})$ rod.

Base: 2mm (1/16") hand spun stainless

steel.

Back plate: investment cast and CNC

machined stainless steel.

Mounting

12 volt - the luminaire is mounted to the wall using two 316 stainless screws through a shallow base 16mm (5/8") in depth. A Wall Box Adaptor Plate is available as an accessory to fit 3.0 and 4.0 junction boxes for USA /Canada. Retro - a mounting plate is fixed to the wall using two screws and then the luminaire is fitted to the mounting plate.

Features

Lens

10mm (3/8") clear, flush fit, tempered, shatter resistant glass.

Lifetime Warranty.

Gasket

Silicone, iron impregnated 220°C (428°F).

Lamp Holders

MR16 & GU10 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) Teflon cables.

Accessories

Cable Joint Kit (Cat. CJK150). Not approved for USA/Canada. Glare Guard (Cat. GG). Hex Cell Louvre (Cat. HCL). Wall Box Adaptor Plate (Cat. WBAP). For 12 luminaires for USA/Canada.

Swivel

Aluminium and Copper luminaires -360° rotation and 0-90° elevation, solid brass with anti rust spring.

Stainless Steel luminaires - 360° rotation and 0-90° elevation, full stainless steel construction.

Standards

IP66, UL1838, **(**)*



Luminaire Weight

12 volt - Aluminium - 0.495kg (1lb 1oz)

Copper - 1.300kg (2lb 13oz)

Stainless Steel - 1.080kg (2lb 6oz)

Retro - Aluminium - 0.900kg (1lb 15oz)

Copper - 1.710kg (3lb 12oz)

Stainless Steel - 1.500kg (3lb 4oz)

Power Supply

12 volt - Hunza Inground or Wall Mount Transformer: not included.

USA and Canada

Hunza Wall Mount Transformer: not included.

Retro - Hunza 110/240-12 volt ac potted electronic transformer built into the Retro base. Dimmable with a suitable dimmer.

Lamp Options


MR16 - 20 or 35 watt lamp max.


GU10 - 25 or 35 watt lamp max.


USA and Canada

MR16 - 20 or 35 watt lamp max.

GU10 - lamp not supplied.









© 2016 Hunza Holdings Ltd.