

Flush Washer PURE LED

PROJECT: _____


TYPE: _____

SOURCE: _____

NOTES: _____

SPECIFICATIONS IK10 IP68


LED Chip	Cree CXA 1304 field replaceable LED board
Luminaire Output	600 Lumens @ 1050mA (9 watts), Delivered from Luminaire with unobstructed beam.
Lumens Per Watt	66 Lumens minimum @ 9 watts, Delivered from Luminaire with unobstructed beam
CRI (3000K)	80 Standard, 90+ Optional
Colour Temperatures	2700K, 3000K, 4000K
Beam Angles	Asymmetric Wash
Ingress Protection	IP68
Inverse Kinematics Rating	IK10
Maximum Load	2000kgs (4400lbs)
Warranty	Electronics = 5 years Body Cop/SS = 10 years Body Aluminium = 5 years
Standards	BS/EN 60598.2.2, 60598.2.18, 60598.1 cUL 1838, 2108 CE



PRODUCT CONFIGURATION

Please fill in appropriate codes into boxes provided

Cat. No. WASH/L



SERIES, REMOTE DRIVER REQUIRED:
Constant current driver
Individual fixtures require 9vdc @ 1050mA maximum.
Stainless steel 9vdc @ 700mA maximum.

12VAC INTEGRAL DRIVER:
Transformer required
Hunza integrated plug and play driver
Input: 9-15VAC.
Output: 9vdc @ D3=350mA, D7=700mA, limited to ≤ 40°C (104°F) ambient temperature in Stainless Steel)

[Click here for Remote Power Supply Guidance Charts](#)

LUMINAIRE CONSTRUCTION

CNC machined from one of the following metals:

Copper:

Body - 88.9mm (3^{1/2}"). Flange - solid copper 115mm (4^{1/2}") rod.

316 Stainless Steel:

Body - 88.9mm (3^{1/2}"). Flange - solid 316 stainless steel 115mm (4^{1/2}")

Step Lens:

10mm (25/64") Extra clear, low iron, shatter resistant glass. Lifetime warranty

Gaskets:

Silicone, iron impregnated 220°C (428°F)

Cable:

Water resistant rubber


Mounting:

The Washer comes with a Flush Mounting PVC canister for casting into the ground, vertical surface or into concrete. Maximum drive over speed 10 kp/h (6mp/h) with a maximum load rating of 2000kgs (4400lbs).

Luminaire Weight:

Stainless Steel 1.7kg (3lbs 12oz)
Solid Copper 1.9kg (4lbs 3oz)

ACCESSORIES




Custom Glare Shield
Must be discussed with the factory

BEAM ANGLES

High efficiency Reflectors. Field replaceable



IES files available for download: hunzalighting.com/downloads



ASYMMETRIC LENS

WIRING GUIDE

Available for download: hunzalighting.com/downloads



Diagrams are a guide only, wire colours and polarity may change depending on fixture and country