

HUNZA FACTORY 130 Felton Mathew Ave Glen Innes Auckland 1072 New Zealand Ph: 64-9-528 9471 Fax: 64-9-528 9361 hunza@hunza.co.nz www.hunza.co.nz

INTERNATIONAL CONTACTS: www.hunza.co.nz/contacts.php

Specifications may change without notice. Manufactured in New Zealand. © 2011 Hunza Holdings Ltd. Ver 1.4

Luminaire Construction

CNC finished machined from one of the following metals:

Investment cast in bronze with forged brass mounting plate.

Investment cast in 316 stainless steel with investment cast 316 stainless steel mounting plate.

Mounting

Mount using a mounting plate fixed to the wall, etc. with 316 stainless screws. The luminaire is then fitted to the back plate using two pan head screws.

Features

2mm (3/32") frosted tempered shatter resistant glass.

Lifetime Warranty.

Gasket:

Lens:

Nytrol 150°c (302°f).

Lamp Holder:

G4 - $350^{\circ}c$ (662[°]f) ceramic multi contact lamp holder with 180°c (356°f) silicone cables.

G9 - 280°c (536°f) ceramic lamp holder with 250°c (480°f) teflon cables.

Accessories:

Cable Joint Kit (Cat. CJK150). Not approved for USA /Canada.

G9 Option (Cat. G9).

Standards IP66 Contraction UL1838

Luminaire Weight

BZ .820kg (1lb 12oz) SS .750kg (1lb 10oz)

Power Supply HUNZA™ Inground or Wall Mount Transformer: not included.

USA and Canada: HUNZA[™] Wall Mount Transformer: not included.

> Luminaire: supplied with G4 5, 10, 20 watt lamp max G9 - 25 watt lamp max.

USA and Canada: G4 5, 10 watt lamp max. G9 - 25 watt lamp max.



