

Constant Current LED Drivers Specification Sheet

					
Product Name	T-ECP4-IF Driver	T-D-LPMC-18 Driver	T-MP15 Driver	T-D-LPC-35 Driver	T-D-93010236 Driver
Product Code	T-ECP4-IF	T-D-LPMC-18	T-MP15	T-D-LPC-35	T-D-93010236
Input v	230v	230v	230v	230v	230v
Output v	3-12v	6-25v	44v	9-48v	12-48v
Output w	350mA CC	350mA 17.5w	60-350mA 15w	700mA 35w	700mA 36w
IP Rating	IP66	IP67	IP20	IP67	IP65
Cable Length	150mm	300mm	None	600mm	IP 500mm / OP 350mm
Dimmable	No	No	No	No	0-10v C.Source
Max Distance	20m	60m	60m	60m	60m
Auto Re-set	Yes	Yes	Yes	Yes	Yes
Mounting	Case or Canister	Case or Canister	Case or Canister	Case or Canister	Case or Canister
Dimensions	38mm x 30mm x 23.5mm	140mm x 30mm x 22mm	19mm x 34mm x 115mm	148mm x 30mm x 40mm	30mm x 41mm x 153mm
LuxR Modux 1	1-2	1-8	1-12	n/a	n/a
LuxR Modux 2	n/a	n/a	n/a	2-10	1-12
LuxR Modux 4	n/a	n/a	n/a	1-8	1-8
Hunza PureLED	RD Mouse (a)	n/a	n/a	1-8 (b)	1-8 (b)

Notes:

- (a) Compatible with Hunza remote driver Mouse Lites
- (b) Border, Euro Spot, Twig, Walkway and, Mouse Lites – 700mA
- (c) All other Hunza PureLED products – 1050mA
- (d) Relates to old version
- (e) Installer to set at 350mA / 700mA / 1050mA

Constant Current LED Drivers Specification Sheet

					
Product Name	T-D-93010235 Driver	T-LPC-35-1050 Driver	T-LD25W-36-C0700 Driver	T-2000B Driver	T-D-LCM25 Driver
Product Code	T-D-93010235	T-LPC-35-1050	T-LD25W	T-2000B	T-D-LCM25
Input v	230v	230v	230v	230v	230v
Output v	12-43v	3-30v	12-36v	18-30v	6-54v
Output w	1050mA 48w	1050mA 33w	700mA	2000mA 60w	350A 18w
IP Rating	IP65	IP67	IP66	IP30	IP20
Cable Length	IP 500mm / OP 350mm	600mm	150mm	150mm	None
Dimmable	0-10v C.Source	No	1-10v	Phase	0-10v
Max Distance	60m	20m	tbc	tbc	60m
Auto Re-set	Yes	Yes	Yes	Yes	Yes
Mounting	Case or Canister	Case or Canister	Case or Canister	Case or Canister	Case or Canister
Dimensions	30mm x 41mm x 153mm	30mm x 40mm x 148mm	80mm x 80mm x 45mm	128mm x 60mm x 32mm	105mm x 68mm x 23mm
LuxR Modux 1	n/a	n/a	n/a	n/a	1-14 @ 350mA (e)
LuxR Modux 2	n/a	n/a	n/a	n/a	1-12 @ 700mA (e)
LuxR Modux 4	n/a	n/a	n/a	n/a	1-6 @ 700mA (e)
Hunza PureLED	1-7 (c)	1-5	High Power 1-2	High Power 2-5 (d)	1-4 @ 1050mA (e)

Notes:

- (a) Compatible with Hunza remote driver Mouse Lites
- (b) Border, Euro Spot, Twig, Walkway and, Mouse Lites – 700mA
- (c) All other Hunza PureLED products – 1050mA
- (d) Relates to old version
- (e) Installer to set at 350mA / 700mA / 1050mA