

Mains Dimming Drivers Specification Sheet

					
Product Name	ELED-20P-C250-700T Driver	ELED-40P-C300-1400T Driver	PCD-40-1050 Driver	PCD-60-2000B Driver	
Product Code	T-ELED-20P-C250-700T	T-ELED-40P-C300-1400T	T-ELED-40-1050T	T-2000B	
Input v	230v	230v	230v	230v	
Output v	3-42v	3-50v	22-38v	18-30v	
Output w	20w	40w	40w	2000mA 60w	
IP Rating	IP20	IP20	IP30	IP30	
Cable Length	None	None	75mm+	150mm	
Dimmable	Leading / Trailing Edge	Leading / Trailing Edge	Mains	Mains	
Max Distance	20m	20m	20m	20m	
Auto Re-set	Yes	Yes	Yes	Yes	
Mounting	Enclosure	Enclosure	Enclosure	Enclosure	
Dimensions	20mm x 30mm x 133mm	20mm x 54mm x 171mm	31mm x 60mm x 145mm	128mm x 60mm x 32mm	
LuxR Modux 1	1-9 @ 350mA	n/a	n/a	n/a	
LuxR Modux 2	1-9 @ 700mA	1-15 @ 700mA	n/a	n/a	
LuxR Modux 4	1-4 @ 700mA	1-8 @ 700mA	n/a	n/a	
Hunza PureLED	n/a	1-6 @ 1050mA	4-6	High Power 2-5	